



DIN 5462 & 5463 UNI 220

HX10 SERIES

10 Spline Parallel Sides, Finishing, Single Thread Right Hand, Lugs, Chamfering

Will Produce			Hob Size			Specify Class B, C, D
Major Dia.	Root Dia.	Key	OD	Length	Bore	
78mm (3.071")	72mm (2.835")	12mm (.472")	3-1/4	3-1/4	1-1/4	HX10-78-72
82mm (3.228")	72mm (2.835")	12mm (.472")	3-1/4	3-1/4	1-1/4	HX10-82-72
88mm (3.465")	82mm (3.228")	12mm (.472")	3-1/2	3-1/4	1-1/4	HX10-88-82
92mm (3.622")	82mm (3.228")	12mm (.472")	3-1/2	3-1/4	1-1/4	HX10-92-82
98mm (3.858")	92mm (3.622")	14mm (.551")	3-1/2	3-1/2	1-1/4	HX10-98-92
102mm (4.016")	92mm (3.622")	14mm (.551")	3-1/2	3-1/2	1-1/4	HX10-102-92
108mm (4.252")	102mm (4.016")	16mm (.630")	3-3/4	3-1/2	1-1/4	HX10-108-102
112mm (4.409")	102mm (4.016")	16mm (.630")	3-3/4	3-1/2	1-1/4	HX10-112-102
120mm (4.724")	112mm (4.409")	18mm (.708")	4	3-1/2	1-1/4	HX10-120-112
125mm (4.921")	112mm (4.409")	18mm (.708")	4	3-1/2	1-1/4	HX10-125-112